

NEW

# 3-inch direct thermal mobile printer

**ARGOX**  
a **ALATO** company

## MP3-200



天時科技有限公司  
**ACTION-PLUS CO., LTD**  
Tel : (852) 2803 0306  
WhatsApp : (852) 9807 7382  
Website: www.action-plus.com.hk

*Lightweight & easy to carry*



### Easy operation & Wi-Fi fast reconnection let you print receipts anywhere

#### Application



##### Transportation and Logistics




##### Field Service



##### Government



#### Product features



##### Increased memory

With 128MB SDRAM & 128MB Flash ROM, MP3-200 can store large data in memory.



##### Bluetooth + Wi-Fi

New Bluetooth + Wi-Fi combo module design, sending and receiving data without any difficulties.



##### Upgraded wireless connectivity

Bluetooth V5.2 & Wi-Fi 802.11 b/g/n wireless connection, providing safe and secure communication.



##### High printing speed

MP3-200 in the printing speed is 67% faster than AME-3230, the maximum speed can reach up to 5ips.

<b>Print Specifications</b>		MP3-200
Printing Method	Direct Thermal	
Printing Resolution	203 dpi(8 dots/mm)	
Printing Speed	Max. 5 ips(127mm/s)	
Printing Length	Max. 40"(1016 mm)	
Printing Width	Max. 2.8"(72 mm)	
Memory	128 MB SDRAM, 128MB Flash ROM	
CPU Type	32 bit RISC microprocessor	
<b>Consumables Specifications</b>		
Sensors	Reflective sensor x 1	
Media Type	Direct thermal receipt, direct thermal labels, die cut, black mark	
Media	Max. width: 3" (76.2mm). Min. width: 1" (25.4mm) Max roll capacity (OD): 2.2" (55.8mm) Core size: 0.25" (6.35mm); 0.5"(12.7mm) Thickness: receipt 2mil~4mil (0.0508mm~0.1016mm), direct thermal labels 6mil (0.15mm~0.16mm)	
<b>Fonts &amp; Symbologies</b>		
Fonts	Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation Soft fonts are downloadable Ability to print any Windows True Type font easily. Support scalable font	
1D Barcodes	PPLA: Code 39 · UPC-A · UPC-E · Code 128 subset A/B/C · EAN-13 · EAN-8 · HBIC · Codabar · Plessey · UPC2 · UPC5 · Code 93 · Postnet · UCC/EAN-128 · UCC/EAN-128 K-MART · UCC/EAN-128 Random weight · Telepen · FIM · Interleaved 2 of 5 (Standard/with modulo 10 checksum/ with human readable check digit/ with modulo 10 checksum & shipping bearer bars) · GS1 Data bar (RSS) PPLB: Code 39 · UPC-A · UPC-E · Matrix 2 of 5 · UPC-Interleaved 2 of 5 · Code 39 with check sum digit · Code 93 · EAN-13 · EAN-8 (Standard, 2 /5digit add-on) · Codabar · Postnet · Code128 subset A/B/C · Code 128 UCC (shipping container code) · Code 128 auto · UCC/EAN code 128 (GS1-128) · Interleave 2 of 5 · Interleaved 2 of 5 with check sum · Interleaved 2 of 5 with human readable check digit · German Postcode · Matrix 2 of 5 · UPC Interleaved 2 of 5 · EAN-13 2/5 digit add-on · UPCA 2/5 digit add-on · UPCE 2/5 digit add-on · 64 Compact Printer Series - User's Manual GS1 Data bar (RSS) PPLZ: Code39 · UPC-A · UPC-E · Postnet · Code128 subset A/B/C · Interleave 2 of 5 · Interleaved 2 of 5 with check sum · Interleaved 2 of 5 with human readable check digit · Code 93 · Code 39 with check sum digit · MSI · EAN-8 · Codabar · Code 11 · EAN-13 · Plessey · GS1 Data bar (RSS) · Industrial 2 of 5 · Standard 2 of 5 · Logmars	
2D Barcodes	PPLA: MaxiCode · PDF417 · Data Matrix (ECC 200 only) · QR code · Composite Codes PPLB: MaxiCode · PDF417 · Data Matrix (ECC 200 only) · QR code · Composite Codes PPLZ: MaxiCode · PDF417 · Data Matrix (ECC 200 only) · QR code · Composite Codes · Aztec Barcode · Micro PDF417	
Graphics	PPLA: PCX, BMP, IMG, HEX and GDI format files PPLB: PCX, BMP, Binary Raster, and GDI PPLZ: GRF, Hex and GDI	
Emulation	PPLA, PPLB, PPLZ, ESCP	
<b>Interface Characteristics and Integration</b>		
Operation Interface	LED Indicator x 4, Button x 2	
Communication Interface	USB, RS-232, BT V5.2LE, WIFI 802.11 b/g/n	
Wireless Security	WEP, WPA-PSK, WPA2-PSK, WPA-ENT/WPA2-ENT: TLS/TTLS/PEAP	
Drivers	Windows Driver for Windows Vista/Win7/Win8/Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver	
Software	BarTender, Printer Tool, Font Utility	
Application	iLabelPrint+	
<b>Operating &amp; Environment Characteristics</b>		
Battery	Rechargeable 7.2V Lithium-ion, 3200mAh	
Power Source	100~240VAC 50~60 Hz input; 9 VDC 1.33 A output	
Operation Environment	Operation Temperature(including battery): 14°F~122°F (-10°C~50°C) Storage Temperature(without battery): -4°F~140°F (-20°C~60°C)	
Agency Listing	CE, FCC,UL, BSMI, RoHS 2.0	
<b>Physical Characteristics</b>		
Drop protection	1.5M	
IP Rating	IP54 (with case)	
Printer Dimensions	W 106mm x H 70mm x D 153mm	
Printer Weight	Approx. 530g (including battery)	
Standard Items	Belt Clip, battery, AC adapter, cleaning tool, quick guide, USB cable	
Optional Items	Shoulder strap, environmental case, Lithium-ion battery, single battery charger, 4 bay battery charger, car charger, RS-232 cable	

\*Argox reserves the right to enhance and modify the specification without prior notice.  
Please check Argox sales representative for most updated specifications.

### Argox Information Co., Ltd.

8F., No. 28, Baogao Rd., Xindian Dist., New Taipei City 231029, Taiwan (R.O.C.)  
Tel: +886-2-8912-1121 Fax: +886-2-8912-1124 <https://www.argoxt.com> <https://www.youtube.com/user/argoxtmkt>  
Copyright © 2024. Argox Information Co., Ltd. All Rights Reserved.

