



Epson TM-T82X

Next generation cost effective POS printer

- Designed for businesses with low volume of POS transactions
- All-in-one box with accessories
- Ease-of-use features
- Ease-of-maintenance features
- Paper saving function
- Features Epson quality and reliability

	天時科技有限公司
	ACTION-PLUS CO., LTD
	Tel : (852) 2803 0306
	WhatsApp : (852) 9807 7382
Website: www.action-plus.com.hk	

Epson TM-T82X



All-In-One-box convenience

- Quick setup guide
- Paper roll
- AC cable
- USB cable (for USB-Serial model)

Saving Paper

Provincial Paper features paper save up to 30%

Max. print speed

200mm/sec

Fast transaction

Auto-cuter

Leaving uncut in center

Paper saving

Reduction to 70%

New Operation Panel Design

Flat and Sharp, front operation

Compatibility

Works in TM-T20 environment

Built-in AC Adapter

Space saving



PRINT SPECIFICATIONS

Product Name	TM-T82X
Print method	Line Thermal
Dot density	203 dpi x 203 dpi
Print speed	Max. 200mm/s
Print width (80mm paper width)	72mm±0.5mm
Fonts	12x24 (Font A), 9x17 (Font B)
Column capacity (80mm paper width)	48 (Font A), 64 (Font B)
Character size	1.25x3 mm (Font A), 0.88x2.13 mm (Font B)
Character set	Alphanumeric 95, International character 18 set, Graphics 128x43 page
Characters	ANK
Barcode	UPC-A, UPC-E, JAN8/EAN 8, JAN13/EAN13, Code39, Code93, Code128, ITF, CODABAR(NW-7), GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1DataBar Expanded
2-Dimensional Symbols	PDF417, QR code, Maxi Code, Two-dimensional GS1 DataBar, Composite Symbology
Paper size (80mm paper width)	79.5±0.5mm
Diameter	83mm
Paper thickness	53-75 µm
Auto cutter	Partial cut (one point in center left uncut)
Sensors	Roll paper end, Cover open
MCBF	60 million lines
MTBF	360,000 hours
Auto cutter life	1.5 million cuts
Head life	100km, 15 million lines
Interface	USB 2.0+RS-232C; Ethernet
AC adapter	Embedded
Power source	AC100~240V, 50~60Hz
Stand-by	Approx. 27.8 W
Receipt printing	Approx. 0.4W
Temperature	Operation 5-45°C / Storage -10-50°C
Humidity	Operation 10-90% / Storage 10-90%
Noise level	Approx. 55 dB (bystander position)
Overall Dimensions	140 mm (W) x 192 mm (D) x 137 mm (H)
Weight	Approx. 1.5kg
Color	EBCK
Installation	Horizontally
Operating systems	Windows, MacOSX, iOS, Android, Linux
Data buffer	Selectable as 45 bytes or 4 KB
What's in the box	Thermal roll paper, User's manual, AC cable, USB cable
Options / Accessories	External buzzer OT-BZ20
Ordering information	C31CH26421 - TM-T82X-421 USB+Serial, C31CH26422 - TM-T82X-422 Ethernet

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON
EXCEED YOUR VISION

Epson Hong Kong Limited

Unit 715-723, 7/F Trade Square, 681 Cheung Sha Wan Road, Cheung Sha Wan, Kowloon, H.K.
*Please call our sales hotlines for demonstration at our showroom.

Epson Authorized Customer Service Centre
Wah Fung Computer Services Ltd.
Unit 901, 9/F, Westin Centre, 26 Hung To Road,
Kwun Tong, Kowloon, Hong Kong

HK Sales Hotline : (852) 2827 8711
HK Technical Hotline : (852) 2827 8911
Macau Hotline : (853) 2850 8065

URL: www.epson.com.hk

SEP19-01-POS