

(602) 9807 7382 Website: www.action-plus.com.hi		
----------------------------------------------------	--	--

D2 series



Your Best Choice in small footprint direct-thermal printer





After





Before



Working bench has no luxury room for bulky printer so things are all cramped together.



Compact design of D2 fits nicely on your working bench and makes your work a pleasant experience.

Application Healthcare



Ticket





Feature-rich to make daily work simple and easy



Clamshell design, easy load The D2 series features a user-friendly clamshell design that allows users to simply open the cover and load media.



Seamless-converting to Argox printers!

Automatic Language Emulation Detection

Automatic adopting commonly used printer control languages for maximized user friendliness. (Auto-Detection & Auto-Conversion)

*Sales representative for demonstration video.



Up to 7-inch per second Printing Speed

Featuring 7-ips printing speed. No compromised printing quality even run at the maximum speed.



Enhanced connectivity The D2 series has built-in USB host, USB device, and it can be expanded

with Ethernet/RS232, Wi-Fi, Bluetooth

v4.2.





Best Label-saving Protocol!

Print Specifications	D2-250	D2-350	
Printing Method	Direct	Fhermal	
Printing Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)	
Printing Speed	Max. 7 ips	Max. 5 ips	
Printing Length	Max. 100"(2540 mm)	Max. 50"(1270 mm)	
Printing Width	Max. 2.13"(54 mm)	Max. 2.24"(56.9 mm)	
Memory		ROM (USB storage up to 32GB)	
CPU Type	32 bit RISC microprocessor		
Consumables Specificatio			
Sensors	Reflective sensor x 1 (movable) & Transmissive sensor x 1 (fixed, 6.27mm offset)		
Media Type	Roll-feed, die-cut, continuous, fan-fold, black mark, tags, ticket in thermal paper or plain paper		
Media	Max. width 60mm. Min. width 12mm. Media thickness: 0.06~0.2mm 5"(127mm) OD on a 1"/1.5" (25.4/38 mm) ID core; 4.5"(114mm) OD on a 0.5" (12.7mm) ID core		
Fonts & Symbologies			
Fonts	Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0 ~ 270 rotation Soft fonts are downloadable Ability to print any Windows True Type font easily. Support scalable font		
1D Barcodes	UPC-A, UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR (NW-7), ITF, Industrial 2of5, MSI, UPCadd-on code, POSTNET, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirecional, GS1DataBar Limited, GS1 DataBar Expanded, GS1DataBar Expanded Stacked		
2D Barcodes	QR Code, PDF417 (includingMicroPDF), Data	aMatrix (ECC200), GS1 DataMatrix, MaxiCode	
Graphics	PPLA: PCX, BMP, IMG, HEX,GDI PPLB: PCX, BMP, Binary raster, GDI PPLZ: GRF, Hex, GDI		
Emulation	PPLA, PPLB, PPLZ		
Interface Characteristics a	and Integration		
Operation Interface	LED Indicator x 2, Button(Feed) x 1		
Communication Interface	USB device, USB host		
Drivers	Windows Driver for Vista/Win7/Win8/Win10, LINUX Driver, macOS Driver, Raspberry Pi Driver		
Software	BarTender, Printer Tool		
Database Link	Argobar Pro support ODBC Database Connection: Excel, CSV, MS Access, MS SQL, Oracle MySQL, dBASE (*.dbf)		
Operating & Environmen	t Characteristics		
Power Source	Universal Switching Power supply. AC input voltage: 100~240V, 50~60Hz. DC Output: 24V, 2.5A		
Operation Environment	Operation Temperature: 41°F~104°F (5°C~40°C), 0% ~ 90% non-condensing, Storage Temperature: -4°F~122°F (-20°C~50°C)		
Agency Listing	CE, FCC, cTUVus, Energy Star, RoHS, BSMI, RCM, CB, BIS		
Physical Characteristics			
	W 116mm x H 170mm x D 215mm		
Printer Dimensions			

*Argox reserves the right to enhance and modify the specification without prior notice. Please check Argox sales representative for most updated specifications.

Optional Items



Full/partial cutter,

guillotine-type



Peeler

WLAN



Bluetooth v4.2 Support BT 4.2 on Android & iOS

RS-232



Ethernet



Tel

■ 天時科技有限公司

ACTION-PLUS CO., LTD : (852) 2803 0306

S : (852) 9807 7382

Website: www.action-plus.com.hk



Argox Information Co., Ltd.

7F., No.126, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.) Tel: +886-2-8912-1121 Fax: +886-2-8912-1124 https://www.argox.com https://www.youtube.com/user/argoxmkt email:service@argox.com Copyright © 2021. Argox Information Co., Ltd. All Rights Re