



AP-2278 Bluetooth 2D Handheld Scanner

 天時科技有限公司
ACTION-PLUS CO., LTD
 Tel : (852) 2803 0306
WhatsApp : (852) 9807 7382
Website: www.action-plus.com.hk

- 2000mA battery, long-lasting battery life, 50,000+ scan times when fully charged
- Bluetooth connection with IOS, Android OS, Windows OS
- Support wall mounted, save space



One-key searching



One-key pairing

Two-keys for factory default



Action-Plus Co. Ltd.

5/F., Shun Kwong Commercial Building, 8 Des Voeux Road West, Sheung Wan, Hong Kong

Phone: +852 2803 0306 WhatsApp: +852 9807 7382 / +853 6688 3894

www.action-plus.com.hk





AP-2278

Bluetooth 2D Handheld Scanner

Performance Parameter			
Light Source	LED White light		
Image sensor	800*600 pixels		
Resolution(maximum)	0.102mm / 4mils		
Print contrast ratio(minimum)	≥20%		
Reading Angle	Pitch: 0-360°; Roll(Tilt): ±60°; Skew (Yaw): ±60°		
Decoding Capability	1D: All standard 1D codes, including GS1 DataBar™ linear code can be automatically distinguished and decoded. 2D: Aztec Code; Data Matrix; MaxiCode; QRCode; HANXIN; MicroQR Code Stack code: GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; GS1 DataBar Composite; MicroPDF417; PDF417.		
Reading Indicators	LED light & Buzzer(adjustable tone and volume)		
Typical depth of Field	Precision Barcode Depth of Field 3.34mil CODE 128 10mm—60mm 5mil CODE128 5mm—90mm 3.34mil EAN-13 10mm—55mm 5mil EAN-13 5mm—85mm 13.34mil EAN-13 20mm—190mm 5mil PDF417 5mm—75mm 10mil PDF417 5mm—190mm	15mil PDF417 10mm—200mm 10mil DM 5mm—100mm 20mil DM 5mm—210mm (The minimum depth of field is determined by the barcode length and scanning angle. It depends on the print resolution, contrast and ambient light.)	
Electrical Parameter			
Current	Working current (Standard): < 270 mA Standby current (Standard): < 35 mA		
Input Voltage	5 VDC (+/- 10%)/500mA		
Environmental Parameter			
ESD protection(Air discharge)	8 kV		
Drop resistance	Withstands repeated drops from 1.2m/4.0ft onto a concrete surface.		
Particulate and water sealing	IP52		
Temperature	Working: 0 to 40 °C Storage: -40 to 70 °C		
Humidity(non-condensing)	5 - 95%		
Ambient light	Indoor: 0 to 6,000 lux; Outdoor: 0 to 86,000 lux		
Cordless Parameter			
Cordless mode	2.4G /Bluetooth		
Transmission distance	2.4G: 100 meters; Bluetooth: 50m (basic on open space)		
Communication mode	Wireless real-time transmission/wired transmission/storage mode		
Battery capacity	2000mAh		
Continuous working time	> 12H		
Charging time	4~5H		
Warranty			
Warranty	1 year		

Action-Plus Co. Ltd.

5/F., Shun Kwong Commercial Building, 8 Des Voeux Road West, Sheung Wan, Hong Kong

Phone: +852 2803 0306 WhatsApp: +852 9807 7382 / +853 6688 3894

www.action-plus.com.hk

