



APC6600 Mobile Computer



This is a highly expandable large-screen rugged handheld computer. Equipped with Qualcomm octa-core processor and Android 11 OS, APC6600 comes with a 5.5-inch HD display, barcode scanning, and NFC functions. The device supports quick charge. The Android 11 with Wi-Fi 6-ready platform for higher data throughput and security that fully satisfy the needs in logistics, warehouse, manufacturing, retail, etc. applications.

Specification

Physical Characteristics

Dimensions	160.0 x 76.0 x 15.5 / 17.0 mm / 6.3 x 2.99 x 0.61 / 0.67 in.
Weight	Android 11: 287g / 10.12 oz.(device with battery)
Keypad	1 power key, 2 scan keys, 2 volume keys
Battery	Removable main battery 5200mAh 5200 mAh optional pistol battery, support QC3.0 and RTC Standby: up to 490 hours (only main battery ; WiFi: up to 470h; 4G: up to 440h) Continuous use: over 12 hours (depending on user environment) Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Display	5.5-inch high definition full display (18:9), IPS IGZO 1440 x 720
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Sensor	Accelerometer sensor, light sensor, proximity sensor, gravity sensor
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; receiver
Card slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	Android 11.0: USB Type-C, USB 3.1, OTG, extended thimble;

Performance

CPU	Android 11: Qualcomm Snapdragon™662 Octa-core, 2.0 GHz
RAM+ROM	4 GB + 64 GB
Expansion	Supports up to 128 GB Micro SD card

Developing Environment

Operating System	Android 11; GMS, 90-day security updates, Android Enterprise Recommended, Zero-Touch, FOTA, Soti MobiControl, SafeUEM supported. Committed support for a future upgrade to Android 12, 13, and Android 14 pending feasibility
SDK	Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20 °C to +50 °C
Storage Temp.	-40°F to 158°F / -40 °C to +70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.8 m / 5.91 ft. drops (at least 20 times) to the concrete across the operating temperature range Multiple 2.4 m / 7.87 ft. drops (at least 20 times) to the concrete after installed rubber bumper
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication

Vo-LTE	Support Vo-LTE HD video voice call
Bluetooth	Android 11: Bluetooth 5.1
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna

WLAN	Support 802.11 a/b/g/n/ac/ax-ready/d/e/h/i/k/r/v, 2.4G/5G dual-band, IPV4, IPV6, 5G PA; Fast roaming: PMKID caching, 802.11r, OKC Operating Channels: 2.4G(channel 1~13), 5G(channel36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132, 136,140,144,149;153;157;161;165), Depends on local regulations Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS,PEAP-GTC,etc.
WWAN (Europe, Asia)	2G: 850/900/1800/1900 MHz 3G: CDMA EVDO: BC0 WCDMA: 850/900/1900/2100MHz TD-SCDMA: A/F(B34/B39) 4G: B1/B3/B5/B7/B8/B20/B38/B39/B40/B41
WWAN(America)	2G: 850/900/1800/1900 MHz 3G: 850/900/1900/2100 MHz 4G: Android 11: B2/B4/B5/B7/B8/B12/B13/B17/B28A/B28B/B38

Data Collection

Camera

Rear Camera	Rear 13MP Autofocus with flash
--------------------	--------------------------------

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

Barcode Scanning

2D Scanner	Zebra: SE4710
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX),etc.